

SPECIFICATIONS

INVO LED Batten Range

The new INVO LED batten fittings are designed to make installation fast and simple and also give the best possible energy savings. To achieve this, we use a very simplistic design. There are just 2 components within our INVO LED Battens Fittings; the LED driver and the LED gear tray, both of which are connected with simple push-fit connections. This allows for a very swift and easy install for the engineers. The very efficient LED means you can use a far lower powered LED fitting to produce equal, if not better, light levels than those already in place, coupled with our market leading 5 year warranty, you get peace of mind, fantastic lighting and amazing paybacks.



			Most Popular
Specification	PD-5ft-24W	PD-5ft-48W	PD-5ft-45W-Modern
Power	24 Watt	48 Watt	45 Watt
Lumen	2100 Lumen	4300 Lumen	4590 Lumen
Beam angle	120°	120°	120°
Dimension	1535 x 69 x 105 mm	1535 x 120 x 105 mm	1525 x 58 x 58 mm

For more information, or to book your FREE audit, call us on 01522 595 858, email enquiries@invodirect.co.uk or visit us at www.invodirect.co.uk





SPECIFICATIONS

INVO Anti Corrosive LED Batten

Our range of anti corrosive LED battens are the perfect choice for performance combined with low energy consumption and high light output. Quick and easy to install with low maintenance costs, this fitting is constructed from polycarbonate, making it shock and impact resistant. Available in a choice of lengths, colours and options, such as with sensor or emergency backup.



Specification	PD-GD-5ft-Anti-24W	PD-GD-5ft-Anti-48W
Power	24 Watt	48 Watt
Power Factor	≥0.9	≥0.9
Lumen	2250 Lumen	4500 Lumen
Beam angle	120°	120°
Dimension	1578 x 90 x 85 mm	1578 x 120 x 85 mm

For more information, or to book your FREE audit, call us on 01522 595 858, email enquiries@invodirect.co.uk or visit us at www.invodirect.co.uk

